

CNC MULTI AXIS CENTER WITH TWO SPINDLES, TWO TURRETS, C-AXIS, Y-AXIS AND DRIVEN TOOLS 数控系统多轴中心带两个主轴、两个刀塔、C 轴、Y 轴和驱动工具		
TECHNICAL SPECIFICATIONS 技术规格		机床型号: TRX-800
TRAVELS: 行程范围:		TRAVELS: 行程范围:
Travel Distance X1-axis: 行程 X1 轴:	165 mm (6.5 in)	230
Travel Distance Z1-axis: 行程 Z1 轴:	700 mm (27.5 in)	800
Travel Distance X2-axis: 行程 X2 轴:	190 mm (7.5 in)	230
Travel Distance Z2-axis: 行程 Z2 轴:	720 mm (28.3 in)	800
Travel Distance B-axis: 行程 B 轴:	± 30~120	±30~120
Travel Distance Y1-axis: 行程 Y1 轴:	100 ±50 mm (3.9 ± 2 in)	100
Travel Distance Y2-axis: 行程 Y2 轴:	100 ± 50 mm (3.9 ± 2 in)	100
CAPACITY: 容量:		CAPACITY: 容量:
Max Turning Diameter (Upper Turret): 最大 转弯直径 (上刀塔):	Ø230 mm (9.1 in)	Φ 450
Max Turning Diameter (Lower Turret): 最大 转弯直径 (下刀塔):	Ø230 mm (9.1 in)	Φ450
Max Turning Length: 最大车削长度:	230 mm (9.1 in)	800
Through Hole Diameter (Left Spindle): 通孔 直径 (左主轴):	Ø68 mm (2.1 in)	68
Through Hole Diameter (Right Spindle): 通 孔直径 (右主轴):	Ø65 mm (2.1 in)	65
SPINDLE (LEFT / RIGHT): 主轴 (左/右):		SPINDLE (LEFT / RIGHT): 主轴 (左/ 右):
Chuck Size: 卡盘尺寸:	Ø200 mm (8 in)	200
Speed: 速度:	5,000 rpm	5000rpm
Power: 功率:	22 kW (30 Hp)	22 kW (30 Hp)
Torque: 扭矩:	208 Nm (153 ft – lbs)	208 Nm (153 ft – lbs)
Tooling: 工具:		Tooling: 工具:
Shank: 刀柄:	BMT-55	BMT55
Turret Stations: 刀塔站:	2 x 12/Turret - Live 2 x 12/刀塔 - 现场	2*16
Boring Bar Diameter: 镗杆直径:	Ø32 mm (1.3 in)	Ø32 mm (1.3 in)
Rotary Tool Speed: 旋转工具速度:	5,000 rpm	5000rpm
Rotary Tool Power: 旋转工具功率:	5.5 kW (7.5 Hp)	3.7KW
Rotary Tool Torque: 旋转工具扭矩:	47 Nm (34.7 ft-lbs)	23.5 Nm
With all standard and optional accessories 配备所有标准和可选附件		

